

DMC-FS3	
Dimensions (W x H x D)	94.9 x 53.4 x 22.5 mm (3.74 x 2.10 x 0.89 in)
Weight	Approx. 118g (0.26lb) Approx.140g with Battery and SD Memory Card (0.31 lb)
Camera Effective Pixels	8.1 Mega pixels
Image Sensor	1/2.5", 8.32 Mega Total Pixels CCD, Primary Color Filter
Optical Zoom	3x
Extra Optical Zoom	<u>4:3 Aspect Ratio:</u> 3.8x for 5Mega, 4.8x for 3Mega, 2Mega, 0.3Mega <u>3:2 Aspect Ratio:</u> 3.8x for 4.5Mega, 4.8x for 2.5Mega <u>16:9 Aspect Ratio:</u> 3.8x for 3.5Mega, 4.8x for 2Mega
Digital Zoom	4x (Max. 12.0 x combined with Optical Zoom without Extra Optical Zoom) (Max. 19.1x combined with Extra Optical Zoom)
Focal Length	f=5.5-16.5mm (35mm Equiv.: 33-100mm)
Lens	LEICA DC VARIO-ELMARIT 6 elements in 5 groups (3 Aspherical Lenses / 4 Aspherical surfaces)
Aperture	Wide: F2.8 / F8 (2 steps) Tele: F5.1 / F14 (2 steps)
Optical Image Stabilizer	MEGA O.I.S. (Mode1/ Mode2)
Focusing Area	Normal: 50cm - infinity Macro / Intelligent AUTO: Wide 5cm / Tele 30cm - infinity
AF Metering	Face / 1-point/ 1-point high speed/ 9-point
Focus	Normal / Macro, Quick AF On/Off
AF Assist Lamp	Yes
ISO Sensitivity	Auto /100 / 200 / 400 / 800 / 1600 (High Sensitivity Mode : Auto(1600 - 6400))
White Balance	Auto / Daylight / Cloudy / Shade / Halogen / White Set White Balance Adjustment (only in underwater mode)
Exposure	Program AE
Exposure Compensation	1/3 EV step, +/-2 EV
Backlight Compensation	Yes (at Intelligent AUTO mode)
Auto (AE) Bracketing	+/- 1/3 EV ~1EV step, 3 frames
Light Metering	Intelligent Multiple
Rec Mode (Mode Dial)	Intelligent AUTO, Normal Picture, Motion Picture, Scene 1, Scene 2
Scene Mode	Portrait, Soft Skin, Scenery, Sports, Night Portrait, Night Scenery, Self-Portrait, Food, Party, Candle Light, Baby1, Baby2, Pet, Sunset, High sensitivity, Hi-Speed Burst, Starry Sky, Fireworks, Beach, Snow, Aerial photo, Underwater
Shutter Speed	8-1/2000 sec, Starry Sky Mode : 15, 30, 60sec.
Self Timer	2sec / 10sec
Auto Review	1sec, 2sec, Zoom, Hold
Color Mode	Standard, Natural, Vivid, Black & White, Sepia, Cool, Warm
Recording Format	Still Image: JPEG(Design rule for Camera File system, based on Exif 2.21 standard) DPOF corresponding Image with audio: JPEG (Design rule for Camera File system, based on Exif 2.21 standard) + QuickTime Motion picture: QuickTime Motion JPEG
Recording Image Size	Still Image: <u>4:3 Aspect Ratio:</u> 3264 x 2448 pixels, 2560 x 1920pixels, 2048 x 1536 pixels, 1600 x 1200 pixels, 640 x 480 pixels <u>3:2 Aspect Ratio:</u> 3264 x 2176 pixels, 2560 x 1712 pixels, 2048 x 1360 pixels <u>16:9 Aspect Ratio:</u>

Commentaire [MEI1]: PLEASE CHECK THE SPEC SHEET TO DELETE THE COLOR NOT AVAILABLE IN YOUR SALES AREA.

	3264 x 1840 pixels, 2560 x 1440 pixels, 1920 x 1080 pixels
Image Quality	Fine / Standard
Motion Picture	<u>4:3 Aspect Ratio: 640 x 480 pixels, 320 x 240 pixels 30 fps, 10 fps</u> <u>16:9 Aspect Ratio: 848 x 480 pixels 30 fps, 10 fps</u>
Burst Shooting Mode	<u>Full-Resolution Image</u> 3 frames/sec Max. 7 images (Standard mode), Max 4 mages (Fine Mode) <u>High-speed Burst Mode:</u> Approx. 7 frames/sec (recorded in 2M for 4:3, 2.5M for 3:2, 2M for 16:9)
Unlimited consecutive shooting	Yes
Intelligent Exposure	No
Digital Red Eye Correction	No
Easy Zoom / Zoom Resume	Yes / No
Zoom in Motion Picture Recording	No
Still Image Rec. with Audio	No
Audio Dubbing	No
Real-time histogram	No
Composition Guide line	Yes (2 patterns)
Built-in-Memory	approx. 50MB
Scene Mode Help Screen	Yes
Auto Angle Detection	Yes
Travel Date / World Time	Yes / Yes
Title Edit	Yes
Text Stamp	Yes
Built-in-Flash	Auto, Auto/Red-eye Reduction, Forced On, Forced Off (Slow Sync./Red-eye Reduction only in Night Portrait/Party/Candle Light mode only) 0.3 - 6.3m (Wide/ISO Auto), 0.3 - 3.4m (Tele/ISO Auto)
LCD Monitor	2.5" TFT LCD Display (230K dots), Field of View : approx. 100% AUTO Power LCD mode, Power LCD mode, High angle mode
Playback mode	[REC]/[Play] Selector switch 30-thumbnail display, 12-thumbnail display, calendar display, zoomed playback (16x max.), playback of favorite pictures, image rotation, Resizing (selectable number of pixels), trimming, protection, aspect conv. DPOF print setting
Slideshow Mode	Yes (duration & effect with music adjustable)
Category Playback	Yes (in slideshow mode and normal playback)
OSD language	English, German, French, Italian, Spanish, Polish, Czech, Hungarian, Russian, Chinese (Traditional), Chinese (Simplified), Netherlandic, Thai, Korean, Turkish, Portuguese, Arabic, Persian, Japanese, Swedish, Danish, Finnish *Vary depending on the sales area.
Recording Media	Built-in Memory SD Memory Card, SDHC Memory Card, MultiMediaCard (Still image only)
Microphone	Yes
Speaker	Yes
Interface	DC Input, AV Output (NTSC/PAL), USB2.0 Full speed
Direct Print	PictBridge
Power	Li-ion Battery Pack (3.6V, 1000mAh) (Included) AC Adaptor (Input: 110-240V AC) (Optional)
Battery life (approx.)	330 pictures (CIPA Standard)*1
Included Software	PHOTOfunSTUDIO -viewer- ArcSoft (MediaImpression / Panorama Maker) USB Driver
Standard Accessories	Battery Charger, Battery Pack, Battery carrying case AV Cable, USB Connection Cable, AC Cable, Strap, CD-ROM

Commentaire [ME12]: PLEASE CHECK THE SPEC SHEET TO DELETE THE LANGUAGE NOT AVAILABLE IN YOUR SALES AREA.

Commentaire [ME13]: (PLEASE CHECK THE SPEC SHEET TO DELETE IF THIS IS NOT AVAILABLE IN YOUR SALES AREA)

